



# Exploration Systems and Technologies

Tony Freeman
Stacey W. Boland
Paul Digiacomo
September 2005










## The needs of an Explorer


- Air to breathe
- Power to run equipment
- H<sub>2</sub>0 a supply of water
- Food
- Fuel to return home
- Mobility to move around
- Hazards warning of and reduced risk of
- Communications








# Robotic missions leading to robotic and human Mars outposts in the Vision for Space Exploration







### Mars exploration




Believing scientific exploration of Mars should be discovery-driven, the Mars Program created "Investigation Pathways"

- Illustrates program options
- Exposes mission options
- Identifies long-lead technology requirements.



## Mars Exploration Program Next Decade Timeline










### Mars Orbiter Laser Altimeter (MOLA)

### Profile over polar ice cap








### Mars Orbiter Laser Altimeter (MOLA)


### **Topographic Map of Mars**





## **Lower-Limit H<sub>2</sub>O Mass Fraction From Neutron Spectrometer**











### H<sub>2</sub>O Ice Exposed at the Surface Near the South Pole








## Something Different



- UHF Radar
- Stanford Odyssey bistatic observations
  - Proposed after detection of UHF specular echo in UHF system test to support Mars relay.
  - Layered model correlates in an intriguing fashion with ODY neutron spectrometer water mass.
- [Callas, Linscott, Gunnarsdottir, Simpson]







# Planning and testing to drive Opportunity down Karatepe slope in Endurance Crater, June 2004





# Mars Exploration Rovers in test with 1997 Sojourner rover










## Geologists in action








### Opportunity spectra





Opportunity APXS spectrum with high sulfur content, implying sulphates and standing water


Jarosite with sulphate and hydroxyl components from *Opportunity*, implying evaporation from a salty brine



## Mars Reconnaissance Orbiter


- launched August 12, 2005

- Study history of water on Mars,
- Seek evidence of sub-surface water.
- Seek water-formed minerals.
- Study atmospheric dust and water distribution.
- Monitor daily global weather.
- Three week launch period, August 10-30, 2005.
- 5.6 Mb/s maximum data rate enables 1 meter resolution over large areas.
- Shallow Subsurface Radar (SHARAD) provided by ASI, Alenia Spazio, University of Rome-INFOCOM.





## Absorption of Water Vapor, Liquid and Solid in the Solar Reflected Spectrum




The absorption bands of the three phases of water near 1000 nm are overlapping, but displaced



### Denali, AK

Radiance Vapor





# Image Results for the Forward Inversion for the Three Phases of Water

- Water vapor ranges from 0.51 to 12.7 mm precipitable water
- Liquid water ranges from 0 to 7.4 mm equivalent path transmittance
- Ice ranges from 0 to 27.9 mm equivalent path transmittance





## Ice, Liquid Water and Water Vapor as Red, Green, Blue Image

Blue displays water vapor. Water vapor is highest in the lower elevations.

Green displays liquid water. Liquid water occurs both as vegetation leaf water and melting snow.

Red displays ice. Non melting snow and ice occurs at high elevation.

Areas that are cyan are high in water vapor and high in vegetation liquid water.

Areas that are yellow are high in liquid water and high in ice. These are melting snow regions.








### Earth & Mars at the Poles

- Mars Phoenix Mission
  - Launch in '-07, land in March 2008
  - EOI Submitted to IPY for Antarctic field experiment















### **Phoenix Lander**

- Phoenix will be the first time that the polar regions on Mars will have been investigated in-situ. All measurements will provide the benchmark for future exploration.
- Phoenix will push the frontier of polar science from Earth-based to solar system-based.
- Phoenix directly enhances the polar observational capability within the solar system, while still complementing the knowledge gain in the Earth's polar regions.







### Demonstrated Benefits of Relay Orbiters





Direct-to-Earth

30 Mbits/sol

1 watt-hour/Mbit

< 1 bps semaphores





MGS



Relay

150 Mbits/sol


0.1 watt-hour/Mbit

8 kbps telemetry


Increased data return

Improved energy efficiency

**EDL** telemetry



Odyssey and MGS have returned over 91% of the MER data




## TODAY: Polar regions of Planets are key to future Exploration Vision → IPY relevance




Earth's Polar regions



**Dry Valleys, Antarctica** 





2008 LRO focus on Poles



Mars: Polar Water






**Phoenix** 2008 at N. Pole History of water and polar climate on Mars





## 2008 Lunar Reconnaissance Orbiter: First Step in the Lunar Exploration Program



**Objective:** The Lunar Reconnaissance Orbiter (LRO) mission objective is to conduct investigations that will be specifically targeted to prepare for and support future human exploration of the Moon.





### **Exploring Earth's Moon**



Topographic data to determine illumination







Image permanently shadowed regions



Map polar ice deposits



Characterize terrain for landing sites







### Robotic Lunar Exploration

"Starting no later than 2008, initiate a series of robotic missions to the Moon to prepare for and support future human exploration activities"

- Space Exploration Policy Directive, January 2004

### Rationale

- Environmental characterization for sate access
- Global topography and targeted mapping for site selection and safety









### Moon Mineral Mapper (M3)

#### **Uniform Full Range Instrument**





Spectroscopic Analysis to Answer the Science Questions and Meet the Mission Requirements


Reflectance Spectra




**Calibrated Spectral** 









M3 Near-IR spectroscopy can uniquely identify the presence of small amounts of OH or H2O

(surface scattered solar radiation).





### Development of Subsurface Active Thermal Probe Technology Testbed

## LECTRONICS MOUNTING PLAT INLET (water) MOTOR (in shell IMMERSION HEATER RESERVOIR PRESSURE VESSEL BOW. JPL

Cryobot

#### **Technology Focus**

The Active Thermal Probe technologies have wide applicability to a variety of mission scenarios. By gaining access to the icy subsurface environment, the technology fosters in-situ science exploration. This Cryobot vehicle can take instrument suites to depth through changing stratification. Instruments can include cameras, spectrometers, and in-situ sampling instruments.


Objectives

- •Develop a cryobot mobility performance model through ice. Design and build prototype system for laboratory tests. Show ability to travel in clear water ice.
- •Testing mobility in ice/sediment environments
- •Tethered field operation and acoustic development
- •Mobility in ice/vacuum and ice transceiver development



### **Europa Subsurface Mission**





#### Critical Technology

- Subsurface Access
- In situ instrumentation
- Contamination control

### Other Important Technology

- Subsurface navigation
- Communications
- Power sources

#### Science Objectives


- Search for evidence of life
- Determine the physical and chemical characteristics of ice
- Determine chemical, physical and biological properties of the ocean

#### Mission Description

- Landing site: Within selected region (thin ice crust or non-deforming ice)
- Subsurface : Descend 5-30km to the ice/water interface
- Telecon/Navigation: In-Ice transceivers and Lander telecom
- Cost: TBD
- Option: Profile Study of Water, Sediments

#### Measurement Strategy

- Determine composition and temperature as the probe descends through the ice
- Image features within the ice and ocean
- Establish ocean observatory at base of ice








### Calipso and Cloudsat Missions

Will provide key measurements of aerosol & cloud properties needed to improve climate predictions

#### **Together, CALIPSO and Cloudsat provide**

- •A global measurement suite from which the first observationally -based estimates of aerosol direct radiative forcing of climate can be made.
- •A dramatically improved empirical basis for assessing aerosol indirect radiative forcing of climate.
- •A factor of 2 improvement in the accuracy of satellite estimates of longwave radiative fluxes at the Earth's surface and in the atmosphere.
- •A new ability to assess cloud-radiation feedback in the climate system.







### **Aeronomy of Ice in the Mesosphere (AIM)**

NASA's Small Explorer Mission to study polar mesospheric clouds PI: Jim Russell/Hampton University

Launch: September 29, 2006

Prime mission: Two years




### **Science Objectives:**


- to determine why polar mesospheric (noctilucent) clouds (PMC'S) form and how they evolve
- to understand the relationship between PMC's and the polar mesosphere
- and thus to provide a basis for study of long-term variability in the mesosphere and its relationship to global change



## **New Capabilities** on the Horizon



Aquarius -- Sea surface salinity



Orbiting Carbon Observatory



**HYDROS** -- Soil Moisture



Innovative Suborbital Platforms -- UAVs, Long-duration Balloons





## Big Science Questions

- Ice Thickness
- Snow water equivalent
- Observation of warm glaciers/ice
- Carbon balance seasonal variations of CO2 and Methane
- How fast does land ice move?
- Precipitation (not a currently viable measurement)



### What Will Be There in 2007-8



### In Space

## Landsat Series (vis/IR) GRACE

DMSP Series (passive microwave, et al)

RADARSAT (interferometric SAR)

NOAA Series (vis/IR)

METEOR-3M (passive microwave, vis/IR)

CARTOSAT-1 (high res optical)

CRYOSAT (radar altimetry)

ALOS (SAR)

TerraSAR-X (imaging microwave radar)

RESOURCESAT-1 (high res optical)

METOP Series (scatterometer, vis/IR)

RISAT-1 (imaging microwave radar)

NPP (sounders, vis/IR)

RapidEye (high res optical)

SPOT (through early 2007 –high res optical, vis/IR)
Envisat (through early 2007 –microwave radar, vis/IR)
Aqua (through early 2007 – passive microwave, sounders)
SICH-1M (through 2007 – microwave radar, et al)
SAOCOM 1 (2008-? –imaging radar, vis/IR)
Pleiades Series (late 2008-? – high res optical)

### In The Field

- 8 ground stations in Alaska used as validation sites (ALECTRA) since mid-90s for NScat
- Field work across Alaskan North Slope for carbon cycle dynamics study

### What is Missing

- Ice thickness measurement
- Snow-water equivalent
- Ground calibration of radar



### What Else Can NASA/JPL Do?



### Technology

- High frequency (Ka/Ku band) SAR for topographic mapping of glaciers and ice sheets
- Low frequency radar (CAS) to get direct measure of ice thickness
- Interferometric Sounder to measure total global ice sheet volume
- -AIRSAR using AVIRIS and MASTER
- UAVSAR to reach larger regions and image ridges in ice

### Increased Collaboration

- Work with ESA for ENVISAT to cover polar regions more thoroughly
- NSF for in situ
- JAXA for ALOS mosaics
- -Antarctic Mapping Mission-3 to produce complete high-res image mosaic of Antarctica to examine change and produce first, complete velocity map of the Antarctic Ice Sheet

### Field Work


- PoleNet backbone ground network to support GPS and seismic network; Technology pathfinder to networks on Mars
- Bedrock crustal motion from GPS ground stations to help interpret GRACE data
- -Ground truth for radar instrument calibration (including geometric)
- Corner reflectors for calibration of radar from space
- -Tumbleweed polar rover for elevation with increased GPS resolution
- -Polar micro stations for year-round weather, ice melt,precise GPS, & magnetometers
- Micro-sub for under ice shelf or under lake investigations


### **Data Fusion**

- Velocity maps from RADAR data
- Freeze-thaw and classification of wetlands for ALOS
- Coupled model of Arctic ocean-sea iceatmosphere (RIMS)




# Recent Airborne Mapping of Changes in Ice Cover





Patagonia and Antarctica surveys










Antarctica - probing the 3rd dimension with lidar

and radar















## **Antarctica: A Snapshot in Time**


### **Mapping the Continent**



**Mapping Velocities** 




Changing ice margins (2000 RADARSAT-1 Image)






# Antarctic Circumpolar Current from GRACE and QuikSCAT



FRONTS of the ANTARCTIC CIRCUMPOLAR CURRENT

BOTTOM PRESSURE DIFFERENCE EQUIVALENT TO UNIFORM TOP-TO-BOTTOM TRANSPORT VARIABILITY (1 CM ~ 2.5\*106 m<sup>3</sup>/s)


EAST WIND, AVERAGED OVER LATITUDES 30S to 65S





# Tandem-X for Ice Applications for IPY: Extend SRTM North and South to complete the Global DEM

Ice Topography Mapping for Change Applications and Mass Balance Studies





### NASA role in Tandem-X

• Polar Interferometric Processing for DEM North of 60° and South of -60° to Polar Science and Applications



SRTM Near-Global Coverage missed critical polar regions





Tandem-X can have excellent height mapping performance at poles



### UAVSAR for RPI Deformation Measurements PL

- · UAVSAR is an new radar instrument designed to have a robust repeat pass radar interferometry capability for measuring rapidly deforming surfaces on a UAV.
- Measuring rapidly deforming surfaces such as from volcanoes, earthquakes or certain glaciers with millimeter accuracy.
- Planned inaugural flight on a Gulfstream III in the Fall of 2006 with first science applications beginning in the in late 2007.
  - Major technical innovations inlcude:
  - -A polarimetric electronically scanned L-band array and associated radar system that is an easily deployed instrument with radar steering that can be linked to on-board INU.
  - -An ability to fly the aircraft based on real-time GPS measurements within a 10 m tube (1 M goal).









## In Situ Work

- 1) Tumbleweed Next round of deployments South Pole, Greenland, Devon Island Elevation with Increased GPS resolution (<1m)
- 2) Micro-Gondolas Multi-day Gondola with science instruments Deployment with NSF (McMurdo) or BAS Rothera
- 3) Ice Probe
- a) Use for Radar (Goggenini) Inclusion/Water Verification
- b) Incorporate Spectrometer
- c) Upgrade current system with smaller/higher res. camera head
- 3) Cryobot Mini-Water Drill Develop a mini water drill for 1-200m drilling with small logistics
- 4) Micro-Sub Develop a micro-sub for:
- a) under ice shelf investigations
- b) Subglacial Lake Investigation
- 5) Polar Rover
- a) Sea Ice Thickness
- b) Radar Based Rover
- 6) Year Round Polar Micro Stations Can be used for:
- a) weather, ice melt, sun radiation
- b) precise GPS, Magnetometers









## Synergy with Mars Program

- Keen interest in aerial platforms within the future Mars program
- Lightweight, low power and compact instruments are key to capable systems

 UAV platforms on Earth can be used as testbeds to demonstrate technology for Mars








MRO (arrive 2006, primary science mission through 2008)

- Charad sounder to sound the ice sheets
- CRISM hyperspectral imager

Mars Phoenix Mission (Launch in '-07, land in March 2008) to confirm the presence of water in polar regions of Mars



DC-8 Flights of AVIRIS and MASTER over Antarctic Dry Valleys would be analogs of CRISM and THEMIS

Keen interest in aerial platforms within the future Mars program UAV platforms on Earth can be used as testbeds to demonstrate technology for Mars











## Volcano Sensorweb Example

Terra/Aqua MODIS Low-Resolution Data (250 m to 1 km/pixel)







No human in the loop!

EO-1 Hyperion:
Obtain HighResolution Data
of Event
(10 m/pixel)

+

Rapid downlink of relevant data






In-situ assets





### The EO-1 Autonomous Sciencecraft




- Autonomy software flying onboard Earth Observing One Spacecraft since Oct. 03
- Onboard software enables spacecraft to autonomously monitor and retarget volcanoes, flooding, cryosphere events
- This software has enabled:
  - > 100x increase in science return
  - \$1.5M/year reduction in operations cost
- In development for MER and Mars Odyssey extended mission
- Co-winner of 2005 NASA Software of the Year Award



## Solid Earth Modeling






### **Technology Accomplishments**

Interoperable web portal modeling environment Enables multiscale earthquake modeling Parallel high performance software:

- GeoFEST: adaptive finite element software
- PARK: fault nucleation boundary element program
- Virtual California: models interacting faults
- Developing parallel tsunami modeling software

### **Science Accomplishments/Progress**

- 16 out of 17 M>5 earthquakes occurred in regions identified by pattern informatics method
- LA basin sediments, and multiple faults control basin shortening
- Modeling current observable strain pattern from the 1906 San Francisco earthquake








### ECCO Analysis Reveals Mediterranean Sea Oscillation

The ECCO model has revealed a new basin-wide sea level fluctuation of the Mediterranean Sea caused by winds in the vicinity of the Strait of Gibraltar.



Fukumori, Menemenlis, and Lee (2005, JPO, submitted)

## Sea level anomalies (cm) relative to mean annual cycle

